



DaVinci Slate

DaVinci Slate is carefully engineered to provide the authentic look and durability of natural slate, while protecting the earth's natural resources and your budget. Available in 11 standard color blends and multiple widths.



Aberdeen



Brownstone



Canyon



Castle Gray



European



Evergreen



Slate Black



Slate Gray



Sonora



Vineyard



Weathered Green



Your Custom Blend

Low Maintenance & Easy Installation

DaVinci Slate multi-width polymer tiles make installation easy—saving materials and cutting down on installation costs. With little to no upkeep and backed by DaVinci's 50-year warranty, DaVinci composite slate tiles are the perfect fit for your home for generations to come.

A Safer & More Secure Roof

DaVinci Slate has achieved the highest possible test ratings for fire, wind and impact giving you a more secure home for your family and has been approved and preferred by cities and subdivisions nationwide.

Specification Chart

Shingle Dimensions

Widths	12", 10", 9", 7", 6"	Thickness at Butt	1/2"
Length	18"	Thickness at Tip	1/8"

Hip - Ridge - Starter

	6" Hip & Ridge (for ridge vents only)	7" Hip & Ridge (standard)	12" Starter
Pieces / Bundle	20	20	20
Lineal Ft / Bundle	5*	5*	20
Pieces / Lineal Ft	4*	4*	1

* At recommended 6" exposure Note: 9" pieces available for ridge; 4" pieces available for turrets.

Field Shingles per Roofing Square

Coursing	Roof Pitch	Max. Exposure	Bundles / Square	Shingles / Square	Weight / Square
Straight	6:12 or greater	7.5"	7.00	210	273 lbs
Staggered	6:12 or greater	7.0"	7.50	225	293 lbs
Straight or Staggered	Less than 6:12	6.0"	8.75	262	342 lbs

Note 1: All calculations are based on using the recommended 3/8" gap between shingles.

Note 2: Straight coursing may be used at any exposure up to 7.5" and staggered coursing may be used at any exposure up to 7.0"

Packing and Shipping Information

	# Shingles	Weight
Per Bundle*	30	39 lbs
Per Pallet**	1,440	1,872 lbs
Per Truckload***	34,560	44,928 lbs

* All weights are approximate ** 48 bundles per pallet *** 24 pallets per truckload

Testing Summary

Type of Test	Standard	Results
Fire Test	ASTM E 108	Class A
Impact Test	UL 2218	Class 4
Wind Test	ASTM D 3161	Certified to 110 MPH

Building Code Approvals: ICC-ES ESR-2119, Miami Dade County, FL NOA No. 06-308.03 Exp. 7/12/12 and TDI

Toll Free: 800-DaVinci (328-4624) Phone: 913-599-0766 Fax: 913-599-0065

www.davinciroofscapes.com