



Valoré Slate

Valoré Slate closely resembles the classic traditional slate tile found on upscale residences throughout the world, but requires none of the maintenance. Available in 8 standard color blends and 12-inch widths.



Cambridge inspired by Brownstone



Milano inspired by European



Sabino inspired by Canyon



Sedona inspired by Sonora



Slate Black



Slate Gray



Verde inspired by Evergreen



Villa inspired by Castle Gray



Your Custom Blend

Low Maintenance & Easy Installation

Valoré Slate polymer roofing tiles make installation easy—saving materials and cutting down on installation costs. With little to no upkeep and backed by DaVinci's 50-year warranty, Valoré Slate tiles are the perfect fit for your home for generations to come.

A Safer & More Secure Roof

Valoré Slate has achieved the highest possible test ratings for fire, wind and impact giving you a more secure home for your family and has been approved and preferred by cities and subdivisions nationwide.

Specification Chart

Shingle Dimensions

Widths	12"	Thickness at Butt	1/2"
Length	18"	Thickness at Tip	1/8"

Hip - Ridge - Starter

	6" Hip & Ridge (for ridge vents only)	7" Hip & Ridge (standard)	12" Starter
Pieces / Bundle	20	20	20
Lineal Ft / Bundle	5*	5*	20
Pieces / Lineal Ft	4*	4*	1

* At recommended 6" exposure Note: 9" pieces available for ridge; 4" pieces available for turrets.

Field Shingles per Roofing Square

Coursing	Roof Pitch	Max. Exposure	Bundles / Square	Shingles / Square	Weight / Square
Straight	6:12 or greater	7.5"	7.1	155	266 lbs
Staggered	6:12 or greater	7.0"	7.6	166	285 lbs
Straight or Staggered	Less than 6:12	6.0"	8.8	194	332 lbs

Note 1: All calculations are based on using the recommended 3/8" gap between shingles.

Note 2: Straight coursing may be used at any exposure up to 7.5" and staggered coursing may be used at any exposure up to 7.0"

Packing and Shipping Information

	# Shingles	Weight
Per Bundle*	22	37 lbs
Per Pallet**	1,056	1,776lbs
Per Truckload***	25,344	42,624lbs

* All weights are approximate ** 48 bundles per pallet *** 24 pallets per truckload

Testing Summary

Type of Test	Standard	Results
Fire Test	ASTM E 108	Class A
Impact Test	UL 2218	Class 4
Wind Test	ASTM D 3161	Certified to 110 MPH

Building Code Approvals: ICC-ES ESR-2119, Miami Dade County, FL NOA No. 06-308.03 Exp. 7/12/12 and TDI

Toll Free: 800-DaVinci (328-4624) Phone: 913-599-0766 Fax: 913-599-0065

www.davinciroofscapes.com