



**ROSS**  
Building Products, LLC

## Ross® Vinyl Locking H-Mold®

U.S. Pat. No. D594,563



### TEN-YEAR LIMITED WARRANTY

**Ross** warrants defective-free products for a period of 10 years for the original purchaser. **Ross** products are further warranted as to adequacy of design, provided products are properly specified and installed. This warranty does not apply in the event products are altered in any way or are improperly installed. Liability is limited to replacement of products proven to be defective. Should any manufacturing defect occur during the 10 year period of the original purchaser (and as long as the original purchaser is still living and retains ownership of the property), **Ross** will provide replacement material for that portion of the product deemed to be defective (not including labor costs incurred in removing defective product or installing replacement product). Proper documentation of date of installation and purchase must accompany any claims for warranty.

**Ross** has made no other warranty, express or implied, regarding its products, including but not limited to, any warranty regarding merchantability or fitness for a specific purpose. Any claim that a product is defective must be brought within 1 month of the date of installation of such products to the original purchaser. Customer hereby agrees that no other incidental or consequential damages are the responsibility of **Ross**.

Responsibility remains with the architect or engineer, contractor and owner for the design, application and proper installation of each **Ross** product. Specifier and user shall determine the suitability of products for specific application and assume all responsibilities in connection there within.

The PVC **Ross** buys is an industry-standard, rigid, durable, chemically resistant product designed for outdoor weatherability. While the PVC is paintable, we cannot know what may be added to paints, primers, etc. that could affect the PVC. Installers must consult with the paint manufacturer's technical department for their specific recommendations on priming and painting PVC. Follow the paint manufacturer's recommendations for paint application. Make sure **Ross** PVC Trim is clean and dry before painting.

*\*PVC products will not support or spread flames. They are self-extinguishing as soon as the flame source is removed.*